

Three Phase String Inverter

FE-30/33/35/36-3P-OG

Feston
always on



2 MPP trackers, Max. efficiency up to 98.6%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



+91 89258 27701



sales@festonsev.com

Technical Data

Model	FE-30-3P-OG		FE-33-3P-OG		FE-35-3P-OG		FE-36-3P-OG			
PV String Input Data										
Max. PV Input Power (kW)			39		42.9		45.5		46.8	
Max. PV Input Voltage (V)			1100							
Start-up Voltage (V)			250							
MPPT Voltage Range (V)			200-1000							
Rated PV Input Voltage (V)			600							
Max. Operating PV Input Current (A)			40+40							
Max. Input Short Circuit Current (A)			60+60							
No. of MPP Trackers/ No. of Strings MPP Tracker			2/3+3							
AC Output Side										
Rated AC Output Active Power (kW)			30		33		35		36	
Max. AC Output Apparent Power (kVA)			33		36.3		38.5		39.6	
Rated AC Output Current (A)			45.5/43.5		50/47.8		53/50.7		54.5/52.2	
Max. AC Output Current (A)			50/47.9		55/52.6		58.3/55.8		60/57.4	
Rated Output Voltage/Range (V)			220/380V, 230/400V 0.85Un-1.1Un							
Grid Connection Form			3L/N/PE							
Rated Output Grid Frequency/Range(Hz)			50/45-55, 60/55-65							
Power Factor Adjustment Range			0.8 leading to 0.8 lagging							
Total Current Harmonic Distortion THDi			<3%							
DC Injection Current			<0.5%In							
Efficiency										
Max. Efficiency			98.6%							
Euro Efficiency			98.1%							
MPPT Efficiency			>99%							
Equipment Protection										
DC Polarity Reverse Connection Protection			Yes							
AC Output Overcurrent Protection			Yes							
AC Output Overvoltage Protection			Yes							
AC Output Short Circuit Protection			Yes							
Thermal Protection			Yes							
DC Terminal Insulation Impedance Monitoring			Yes							
DC Component Monitoring			Yes							
Ground Fault Current Monitoring			Yes							
Arc Fault Circuit Interrupter (AFCI)			Optional							
Power Network Monitoring			Yes							
Island Protection Monitoring			Yes							
Earth Fault Detection			Yes							
Overvoltage Load Drop Protection			Yes							
Residual Current (RCD) Detection			Yes							
Surge Protection Level			TYPE II(DC), TYPE II(AC)							
Interface										
Communication Interface			RS485/RS232							
Monitor Mode			GPRS/WIFI/Bluetooth/4G/LAN(optional)							
General Data										
Operating Temperature Range (°C)			-25 to +60°C, >45°C Derating							
Permissible Ambient Humidity			0-100%							
Permissible Altitude (m)			4000m							
Noise (dB)			≤60							
Ingress Protection(IP) Rating			IP 65							
Inverter Topology			Non-Isolated							
Over Voltage Category			OVC II(DC), OVC III(AC)							
Cabinet Size (WxHxD mm)			330×572×206 (Excluding Connectors and Brackets)							
Weight (kg)			28.7							
Warranty			10 Years							
Type of Cooling			Intelligent Air Cooling							
Grid Regulation			IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UN217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105							
Safety EMC/Standard			IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2							

FESTON S.E.V PRIVATE LIMITED

No.97/80, Vanagaram Service Road, Athipet, Ambattur, Chennai - 600 058, TN, INDIA.

Three Phase String Inverter

FE-40/45/50-3P-OG

Feston
always on



Max. 4 MPPT trackers, Max. efficiency up to 98.7%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

+91 89258 27701

sales@festonsev.com

Technical Data

Model	FE-40-3P-OG	FE-45-3P-OG	FE-50-3P-OG
PV String Input Data			
Max. PV Input Power (kW)	52	58.5	65
Max. PV Input Voltage (V)	1100		
Start-up Voltage (V)	250		
MPPT Voltage Range (V)	200-1000		
Rated PV Input Voltage (V)	600		
Max. Operating PV Input Current (A)	40+40+40		40+40+40+40
Max. Input Short Circuit Current (A)	60+60+60		60+60+60+60
No. of MPP Trackers/ No. of Strings MPP Tracker	3/3+3+3		4/3+3+3+3
AC Output Side			
Rated AC Output Active Power (kW)	40	45	50
Max. AC Output Apparent Power (kVA)	44	49.5	55
Rated AC Output Current (A)	60.6/58	68.2/65.2	75.8/72.5
Max. AC Output Current (A)	66.7/63.8	75/71.7	83.3/79.7
Rated Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un		
Grid Connection Form	3L/N/PE		
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65		
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Total Current Harmonic Distortion THDi	<3%		
DC Injection Current	<0.5In		
Efficiency			
Max. Efficiency	98.7%		
Euro Efficiency	98.1%		
MPPT Efficiency	>99%		
Equipment Protection			
DC Polarity Reverse Connection Protection	Yes		
AC Output Overcurrent Protection	Yes		
AC Output Overvoltage Protection	Yes		
AC Output Short Circuit Protection	Yes		
Thermal Protection	Yes		
DC Terminal Insulation Impedance Monitoring	Yes		
DC Component Monitoring	Yes		
Ground Fault Current Monitoring	Yes		
Arc Fault Circuit Interrupter (AFCI)	Optional		
Power Network Monitoring	Yes		
Island Protection Monitoring	Yes		
Earth Fault Detection	Yes		
Overvoltage Load Drop Protection	Yes		
Residual Current (RCD) Detection	Yes		
Surge Protection Level	TYPE II(DC), TYPE II(AC)		
Interface			
Communication Interface	RS485/RS232		
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)		
General Data			
Operating Temperature Range (°C)	-25 to +60°C, >45°C Derating		
Permissible Ambient Humidity	0-100%		
Permissible Altitude (m)	4000m		
Noise (dB)	<65		
Ingress Protection(IP) Rating	IP 65		
Inverter Topology	Non-Isolated		
Over Voltage Category	OVC II(DC), OVC III(AC)		
Cabinet Size (WxHxD mm)	434×570×243 (Excluding Connectors and Brackets)		
Weight (kg)	39		
Warranty	10 Years		
Type of Cooling	Intelligent Air Cooling		
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UN217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105		
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2		

FESTON S.E.V PRIVATE LIMITED

No.97/80, Vanagaram Service Road, Athipet, Ambattur, Chennai - 600 058, TN, INDIA.