

Hybrid Inverter

FES-HB-LV-1P(8KW)



Colorful touch LCD, IP65 protection degree



DC couple and AC couple to retrofit existing solar system

16

Max.16 pcs parallel for on-grid and off-grid operation: Support multiple batteries parallel

190

Max. charging/discharging current of 190A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator



+91 89258 27701



sales@festonsev.com

Technical Data

Model	FES-8K-1PH-HB
Battery Input Data	
Battery Type	Lead-acid or Li-Ion
Battery Voltage Range (V)	40~60
Max. Charging Current (A)	190
Max. Discharging Current (A)	190
External Temperature Sensor	Yes
Charging Curve	3 Stages / Equalization
Charging Strategy for Li-Ion Battery	Self-adaption to BMS
PV String Input Data	
Max. DC Input Power (W)	10400
Rated PV Input Voltage (V)	370 (125~500)
Start-up Voltage (V)	125
MPPT Voltage Range (V)	150-425
Full Load DC Voltage Range (V)	200-425
PV Input Current (A)	26+26
Max. PV ISC (A)	34+34
Number of MPPT / Strings per MPPT	2/2+2
AC Output Data	
Rated AC Output and UPS Power (W)	8000
Max. AC Output Power (W)	8800
AC Output Rated Current (A)	36.4
Max. AC Current (A)	40
Max. Continuous AC Passthrough (A)	50
Peak Power (off grid)	2 time of rated power, 10 S
Power Factor	0.8 leading to 0.8 lagging
Output Frequency and Voltage	50/60Hz; L/N/PE 220/230Vac (single phase)
Grid Type	Single Phase
DC injection current (mA)	THD<3% (Linear load<1.5%)
Efficiency	
Max. Efficiency	97.60%
Euro Efficiency	97.00%
MPPT Efficiency	99.90%
Protection	
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection
Output Over Voltage Protection	DC Type II/AC Type III
Certifications and Standards	
Grid Regulation	IEC 62116, IEC 61727
Safety EMC / Standard	IEC 61000-6-1/2/3/4, IEC 62109-1, IEC 62109-2
General Data	
Operating Temperature Range (°C)	-45~60°C, >45°C derating
Cooling	Natural cooling
Noise (dB)	<30 dB
Communication with BMS	RS485; CAN
Weight (kg)	24
Size (mm)	330W x 580H x232D
Protection Degree	IP65
Installation Style	Wall-mounted
Warranty	5 years